



The valve is the crucial part of any sampling system. Based on the process conditions we will select the right valve for the application (both physically and chemically compatible).

A wide range of valves (both make and type) can be used in Dopak samplers, such as needle valves, instrumentation ball valves and process (in-line) valves. Many of the valves are able to meet the standards required (e.g. NACE, Tüv), and are available in threaded and/or flanged connections (ANSI, ASME, DIN).

**Valve body material options may include:**

- SS316 (Standard)
- M400 (Monel)
- HC276 (Hastelloy)
- I825 (Incoloy)
- I625 (Inconel)

**Seat material options:**

- PTFE (Teflon) (Standard)
- PEEK
- PCTFE
- Metal

**Elastomer material (O-rings), options:**

- FKM (Viton) (Standard)
- FFKM (Kalrez)
- TCV (Teflon coated Viton)
- EPDM

For more information please contact our sales department at Bergschenhoek or Houston or your local representative.

**Dopak Inc.**

Houston, Texas 77041, USA  
Phone 713-460-8311  
Fax 713-460-8578  
E-mail info@dopak.com

**Dovianus BV**

Bergschenhoek, The Netherlands  
Phone +31 10 524 20 00  
Fax +31 10 524 20 29  
E-mail info@dopak.nl

Your local representative

