



Different types of handles have been developed, serving the market's demand for more safety and ergonomics. Dopak spring return handles are suited for almost all valves used in Dopak sampling systems and significantly improve operator safety. When the handle is released, the sample valve returns to the "off" position.

Adding a Dopak spring return handle means improved safety for the operator and the environment. So depending on your specific functionality, the following range of Dopak spring return handles for the sampling system can be offered:

- SR 0-90 operation** Manually operated 90° and when released, (spring) forced to off
- SR 0-180 operation** Manually operated 180° and when released, (spring) forced to off
- SR 90-0-90 operation** Manually operated 90° left or right and when released, (spring) forced to off
- SR 90 (fixed)-0-90 operation** When the handle is pulled out, the spring turns 90° for any required time. Then can be manually operated 180° and when released, spring (forced) to off.

Fixed sequence manually operated in each position clock-wise (no spring return)

For more information please contact our sales department at Bergschenhoek or Houston or your local representative.

Dopak Inc.
Houston, Texas 77041, USA
Phone 713-460-8311
Fax 713-460-8578
E-mail info@dopak.com

Dovianus BV
Bergschenhoek, The Netherlands
Phone +31 10 524 20 00
Fax +31 10 524 20 29
E-mail info@dopak.nl

Your local representative

